

住宅用ロックウール断熱材製品一覧
*** 一覧中は全てJIS A 9521 建築用断熱材 の対象品です。**

製品名	品番	JIS認証種類 密度(kg/m ³)	厚さ (mm)	幅 (mm)	長さ (mm)	入数 (枚/梱)	相当 施工面積 (坪/梱)	熱伝導率 (W/m・K) 平均温度 23℃	熱抵抗値 (m ² ・K/W) 平均温度23℃
ロックセラム サイレント	BHS4161M	MB (40以上)	161	425	1380	5	約1.0	0.037	4.4
	BHS410AL	MB (40以上)	100	390	2880	4	約1.6	0.037	2.7
	BHS410L			425	1360	7	約1.4		
	BHS410W			470					
アムマット プレミアム	BHP3155	MA (30以上)	155	425	1360	6	約1.2	0.038	4.1
	BHP3140S	MA (30以上)	140	425	1180	7	約1.2	0.038	3.7
	BHP3105AL	MA (30以上)	105	390	2880	5	約2.0	0.038	2.8
	BHP3105L			425	1360	4	約1.6		
	BHP3105			470		9	約1.7		
	BHP3105WL				4				
	BHP390AL	MA (30以上)	92	390	2880	5	約2.0	0.038	2.4
	BHP390L			425	1360	11	約2.1		
	BHP390			470		5	約2.2		
	BHP390WL								
BHP389BL	MA (30以上)	89	370	2600	6	約2.1	0.038	2.3	
BHP389L			425	2600					
アムマット	BHM3155	MA (30以上)	155	425	1360	6	約1.2	0.038	4.1
	BHM3155W			470			約1.3		
	BHM3140A	MA (30以上)	140	390	1360	8	約1.5	0.038	3.7
	BHM3140			425	1180	7	約1.4		
	BHM3140S			470			約1.2		
	BHM3105AL	MA (30以上)	105	390	2880	5	約2.0	0.038	2.8
	BHM3105L			425	1360	4	約1.6		
	BHM3105			470		9	約1.7		
	BHM3105W				8				
	BHM310AL	MA (30以上)	100	390	2880	5	約2.0	0.038	2.6
	BHM310L			425	1360	10	約1.9		
	BHM310			470		9			
	BHM310W								
	BHM390AL	MA (30以上)	92	390	2880	6	約2.4	0.038	2.4
	BHM390AS			1180	13	約2.1			
	BHM390L			2880	5	約2.0			
	BHM390			425	1360	11	約2.1		
	BHM390S			1180	13				
	BHM390W			470	1360	10			
	BHM375AL	MA (30以上)	77	390	2880	7	約2.8	0.038	2.0
	BHM375L			425	1360	6	約2.4		
	BHM375			470		14	約2.6		
	BHM375W				12	約2.5			
BHM355AL	MA (30以上)	55	390	2880	10	約4.0	0.038	1.4	
BHM355L			425	1360	9	約3.6			
BHM355			1180		19	約3.5			
BHM355S					21				
BHM355W			470	1360	17				
アムマット 天井2枚重ね用	BHM310WT	MA (30以上)	100	470	1360	9	約1.9	0.038	2.6
ロックセラムマット	BH0410FA	MB (40以上)	100	390	1360	8	約1.5	0.037	2.7
	BH0410F			425					
	BH0410FW			470			7		
	BH0455FA		55	390	1360	16	約3.0	0.037	1.5
	BH0455F			425					
	BH0455FW			470			15		
ロックセラムフェルト	BD04010P	MB (40以上)	100	910	5500	1	1.5	0.037	2.7
	BF04050B		50		11000		3		1.4

2025年4月21日時点